




ETN ISY-HOOK n° A.24.08620

Modules validés – validated modules

Manufacturer	Module reference	Peak power		Length	Width	Thickness	Weight
		min	max				
AIKO	AIKO-Axxx-MAH54Db (2S+)	440 Wp	455 Wp	1722 mm	1134 mm	30 mm	24,0 kg
	AIKO-Axxx-MAH54Mb (2S)	445 Wp	460 Wp	1722 mm	1134 mm	30 mm	21,2 kg
AKCOME	SK8610HDGDC	380 Wp	400 Wp	1755 mm	1038 mm	30 mm	22,8 kg
AMERISOLAR	AS-7M108-HC-xxxW	400 Wp	415 Wp	1722 mm	1134 mm	30 mm	20,0 kg
ASTRONERGY	CHSM54N-HC	425 Wp	445 Wp	1722 mm	1134 mm	30 mm	21,3 kg
	CHSM54N(DG)/F-HC	425 Wp	440 Wp	1722 mm	1134 mm	30 mm	20,8 kg
	CHSM54N(BL)/(BLH)-HC	420 Wp	440 Wp	1722 mm	1134 mm	30 mm	21,3 kg
	CHSM54N(DGT)/F-BH	415 Wp	430 Wp	1722 mm	1134 mm	30 mm	20,8 kg
	CHSM54RNs(DG)/F-BH	435 Wp	450 Wp	1762 mm	1134 mm	30 mm	21,5 kg
	CHSM54RNs(DG)/F-BH (2mm+2mm)	445 Wp	465 Wp	1762 mm	1134 mm	30 mm	24,9 kg
	CHSM54RNs(DG)(BLH)/F-BH	430 Wp	450 Wp	1762 mm	1134 mm	30 mm	21,5 kg
	CHSM54RNs(DG)(BLH)/F-BH (2mm+2mm)	440 Wp	460 Wp	1762 mm	1134 mm	30 mm	24,9 kg
	CHSM54RNs(DGT)(BLH)/F-BH	430 Wp	450 Wp	1762 mm	1134 mm	30 mm	21,5 kg
	CHSM54RNs(DGT)(BLH)/F-BH (2mm+2mm)	440 Wp	460 Wp	1762 mm	1134 mm	30 mm	24,9 kg
	CHSM54RNs(DGT)/F-BH	430 Wp	450 Wp	1762 mm	1134 mm	30 mm	21,5 kg
	CHSM60RNs(DGT)(BLH)/F-BH (2mm+2mm)	490 Wp	515 Wp	1961 mm	1134 mm	30 mm	27,4 kg
	Canadian Solar	CS3L-XXXMS	360 Wp	385 Wp	1765 mm	1048 mm	35 mm
CS6R-xxxH-AG		405 Wp	430 Wp	1722 mm	1134 mm	30 mm	23,0 kg
CS6R-xxxMS		395 Wp	420 Wp	1722 mm	1134 mm	30 mm	21,3 kg
CellKraft	CK500M-132	500 Wp	500 Wp	2094 mm	1134 mm	30 mm	29,0 kg
DMEGC	DMxxxM10-66HBB-V	485 Wp	500 Wp	2094 mm	1134 mm	35 mm	26,6 kg
	DMxxxM6-60HBW	375 Wp	385 Wp	1755 mm	1038 mm	35 mm	21,0 kg
	DMxxxM10RT-54HBW	425 Wp	450 Wp	1762 mm	1134 mm	30 mm	20,6 kg
	DMxxxM10RT-54HBW-V	425 Wp	450 Wp	1762 mm	1134 mm	30 mm	20,6 kg
	DMxxxM10RT-54HSW	425 Wp	450 Wp	1762 mm	1134 mm	30 mm	20,6 kg
	DMxxxM10RT-54HSW-V	425 Wp	450 Wp	1762 mm	1134 mm	30 mm	20,6 kg
	DMxxxM10RT-60HBB/HBB-V	480 Wp	500 Wp	1950 mm	1134 mm	30 mm	22,7 kg
	DMxxxM10RT-B54HBW	425 Wp	450 Wp	1762 mm	1134 mm	30 mm	24,5 kg
	DMxxxM10RT-B54HSW	425 Wp	450 Wp	1762 mm	1134 mm	30 mm	24,5 kg
	DMxxxM10RT-B54HST	425 Wp	450 Wp	1762 mm	1134 mm	30 mm	24,5 kg
	DMxxxM10RT-B54HBT	425 Wp	450 Wp	1762 mm	1134 mm	30 mm	24,5 kg
	DMxxxM10RT-G54HBW	425 Wp	455 Wp	1762 mm	1134 mm	30 mm	24,5 kg
	DMxxxM10RT-G54HSW	425 Wp	455 Wp	1762 mm	1134 mm	30 mm	24,5 kg
	DMxxxM10RT-B60HBB	480 Wp	500 Wp	1950 mm	1134 mm	30 mm	27,1 kg
	DMxxxM10T-B54HSW	405 Wp	450 Wp	1722 mm	1134 mm	30 mm	23,6 kg
	DMxxxM10T-B54HBW	405 Wp	450 Wp	1722 mm	1134 mm	30 mm	23,6 kg
	DMxxxM10T-B54HST	405 Wp	450 Wp	1722 mm	1134 mm	30 mm	23,6 kg
	DMxxxM10T-B54HBT	405 Wp	450 Wp	1722 mm	1134 mm	30 mm	23,6 kg






ETN ISY-HOOK n° A.24.08620

Modules validés – validated modules

Manufacturer	Module reference	Peak power		Length	Width	Thickness	Weight
		min	max				
DOMOS	DGE 500 BIV BF	480 Wp	515 Wp	1960 mm	1134 mm	30 mm	27,6 kg
DualSun	SPRING - DSTFxxx-108M10TB-03	420 Wp	430 Wp	1722 mm	1134 mm	30 mm	32,0 kg
	SPRING - DSTlxxx-108M10TB-03	420 Wp	430 Wp	1722 mm	1134 mm	30 mm	32,5 kg
	SPRING - DSTNxxx-108M10TB-03	420 Wp	430 Wp	1722 mm	1134 mm	30 mm	31,0 kg
	FLASH - DSxxx-108M10RTB-03	425 Wp	450 Wp	1762 mm	1134 mm	30 mm	24,5 kg
	FLASH - DSxxx-108M10TB-03	405 Wp	430 Wp	1722 mm	1134 mm	30 mm	25,1 kg
	FLASH - DSxxx-120M10TB-03	485 Wp	500 Wp	1950 mm	1134 mm	30 mm	27,1 kg
	FLASH - DSxxx-132M10-01	480 Wp	505 Wp	2094 mm	1134 mm	35 mm	26,0 kg
DUONERGY	ACN-120FB-HJT	375 Wp	375 Wp	1755 mm	1038 mm	40 mm	23,5 kg
	ACN-132FB-IBC	430 Wp	430 Wp	1895 mm	1039 mm	40 mm	28,0 kg
	DN-BB132-IBC	415 Wp	435 Wp	1895 mm	1039 mm	40 mm	28,0 kg
	DN-BT108N-2	395 Wp	435 Wp	1722 mm	1134 mm	30 mm	24,5 kg
	DN-BT120HJT-2	380 Wp	400 Wp	1755 mm	1038 mm	40 mm	23,5 kg
	DN-BT120HJT-A	375 Wp	395 Wp	1755 mm	1038 mm	30 mm	22,8 kg
	DN-BT108N-3	425 Wp	425 Wp	1722 mm	1134 mm	30 mm	23,6 kg
	DN-BT132N	500 Wp	500 Wp	2094 mm	1134 mm	30 mm	30,2 kg
	DN-BB132-IBC	430 Wp	430 Wp	1895 mm	1039 mm	30 mm	28,0 kg
	DN-BT108N-4	450 Wp	450 Wp	1762 mm	1134 mm	30 mm	24,5 kg
	DN-BT120N-1	500 Wp	500 Wp	1950 mm	1134 mm	30 mm	26,8 kg
Eco Green Energy	EGE-xxx-120M(M6)	350 Wp	375 Wp	1763 mm	1040 mm	35 mm	20,5 kg
	EGE-xxx-132M(M10)	500 Wp	500 Wp	2073 mm	1134 mm	35 mm	21,8 kg
	EGE-xxx-144M(M6)	445 Wp	455 Wp	2102 mm	1040 mm	35 mm	24,5 kg
ECOYA	JNMM120-xxx (L)	360 Wp	380 Wp	1755 mm	1038 mm	30 mm	19,3 kg
	JY3MxxxH60(H)	365 Wp	400 Wp	1755 mm	1038 mm	40 mm	20,0 kg
	TD-xxxMB-120HCxxx	360 Wp	375 Wp	1755 mm	1038 mm	30 mm	18,5 kg
ET Solar	ET-M660BHxxxBB	355 Wp	375 Wp	1755 mm	1138 mm	35 mm	20,0 kg
FHE	FHE - 425W BV - MASTER	425 Wp	425 Wp	1722 mm	1134 mm	30 mm	22,0 kg
	FHE - 425W BVB - MASTER	425 Wp	425 Wp	1722 mm	1134 mm	30 mm	22,0 kg
	FHE - 425W BVN - MASTER	425 Wp	425 Wp	1722 mm	1134 mm	30 mm	22,0 kg
	FHE - 500W SP - MASTER	500 Wp	500 Wp	2094 mm	1134 mm	30 mm	26,0 kg
	FHE - 500W - BVN - MASTER	500 Wp	500 Wp	1961 mm	1134 mm	30 mm	27,6 kg
French Solar Industry	FSI120-xxx-M12	575 Wp	610 Wp	2172 mm	1303 mm	35 mm	30,9 kg
	FSI120-xxx-M6	375 Wp	375 Wp	1754 mm	1038 mm	30 mm	23,0 kg
	FSI-MC-108-BD	428 Wp	428 Wp	1721 mm	1133 mm	30 mm	22,0 kg
Hyundai	HiE-SxxxUF	375 Wp	375 Wp	1646 mm	1140 mm	35 mm	20,5 kg
	HiE-SxxxVG	390 Wp	410 Wp	1719 mm	1140 mm	35 mm	22,0 kg

New





ETN ISY-HOOK n° A.24.08620

Modules validés – validated modules

Manufacturer	Module reference	Peak power		Length	Width	Thickness	Weight
		min	max				
JNL SOLAR	JLS108M	390 Wp	410 Wp	1724 mm	1134 mm	30 mm	21,5 kg
	JLS120M	360 Wp	380 Wp	1755 mm	1038 mm	30 mm	19,3 kg
	JLS120Mxxx - SUNMAX	360 Wp	380 Wp	1755 mm	1038 mm	30 mm	20,5 kg
	JLSDGxxxN-108M10 – Optimax – FB	410 Wp	440 Wp	1722 mm	1134 mm	30 mm	23,3 kg
	JLSDGxxxN-108M10 – Optimax – transp.	415 Wp	440 Wp	1722 mm	1134 mm	30 mm	23,3 kg
	JLSDG120RxxxW - Optimax+ - FB	470 Wp	500 Wp	1955 mm	1134 mm	35 mm	26,5 kg
LONGi	LR5-54HABB-xxxM	390 Wp	415 Wp	1722 mm	1134 mm	30 mm	22,5 kg
	LR5-54HABD-xxxM	395 Wp	420 Wp	1722 mm	1134 mm	30 mm	22,5 kg
	LR5-54HIBD-xxxM	390 Wp	425 Wp	1722 mm	1134 mm	30 mm	22,5 kg
	LR5-54HIH-xxxM	400 Wp	415 Wp	1722 mm	1134 mm	30 mm	20,8 kg
	LR5-54HPB-xxxM	400 Wp	420 Wp	1722 mm	1134 mm	30 mm	20,8 kg
	LR5-54HPH-xxxM	405 Wp	425 Wp	1722 mm	1134 mm	30 mm	20,8 kg
	LR5-54HTB-xxxM (Explorer)	410 Wp	430 Wp	1722 mm	1134 mm	30 mm	20,8 kg
	LR5-54HTB-xxxM (Scientist)	435 Wp	445 Wp	1722 mm	1134 mm	30 mm	20,8 kg
	LR5-54HTD-xxxM	415 Wp	440 Wp	1722 mm	1134 mm	30 mm	22,5 kg
	Exclusivity ! LR5-54HTDB-xxxM (Artist Ultra Black)	415 Wp	430 Wp	1722 mm	1134 mm	30 mm	22,5 kg
	LR5-54HTH-xxxM (Explorer)	415 Wp	435 Wp	1722 mm	1134 mm	30 mm	20,8 kg
	LR5-54HTH-xxxM (Scientist)	440 Wp	450 Wp	1722 mm	1134 mm	30 mm	20,8 kg
	LR5-66HPH-xxxM	495 Wp	515 Wp	2094 mm	1134 mm	35 mm	26,0 kg
	LR5-72HBD-xxxM (30mm)	540 Wp	560 Wp	2278 mm	1134 mm	30 mm	31,8 kg
	LR5-72HBD-xxxM (35mm) - 1133	530 Wp	550 Wp	2278 mm	1133 mm	35 mm	32,3 kg
	LR5-72HBD-xxxM (35mm) - 1134	540 Wp	560 Wp	2278 mm	1134 mm	35 mm	32,6 kg
	LR5-72HPH-xxxM	545 Wp	565 Wp	2278 mm	1134 mm	35 mm	27,5 kg
	RISEN	Titan S G5.3 RSM40-8-xxxM	390 Wp	410 Wp	1754 mm	1096 mm	30 mm
SOLUXTEC	DMMXSCNi-XXX	415 Wp	425 Wp	1722 mm	1133 mm	30 mm	21,5 kg
TONGWEI	THxxx-xxxPMB7-44SCF	400 Wp	425 Wp	1812 mm	1096 mm	30 mm	20,8 kg
	THxxx-xxxPMB7-44SCS	405 Wp	430 Wp	1812 mm	1096 mm	30 mm	20,8 kg
	THxxx-xxxPMB7-46SCF	420 Wp	445 Wp	1899 mm	1096 mm	30 mm	21,8 kg
	THxxx-xxxPMB7-46SCS	420 Wp	445 Wp	1899 mm	1096 mm	30 mm	21,8 kg
Trina Solar	TSM-xxxDE09.08	390 Wp	405 Wp	1754 mm	1096 mm	30 mm	21,0 kg
	TSM-xxxDE09R.05	405 Wp	425 Wp	1762 mm	1134 mm	30 mm	21,8 kg
	TSM-xxxDE09R.08	415 Wp	435 Wp	1762 mm	1134 mm	30 mm	21,8 kg
	TSM-xxxDE18M(II)	485 Wp	510 Wp	2187 mm	1102 mm	35 mm	26,5 kg
	TSM-xxxNEG9R.28	415 Wp	450 Wp	1762 mm	1134 mm	30 mm	21,8 kg

Service client – Customer service

+33.4.42.32.77.80 | contact@isy-pv.com

Support Technique – Technical support

+33.6.65.65.88.86 | technique@isy-pv.com

